


# Technical data sheet



## QUICK-LOCK mini DN 100-DN 125

Quick-Lock Mini	EPDM Rubber	Total diameter rolled	Suitable for pipes from / to		Packer	Stainless steel sleeve			EPDM Rubber	
			Pipe ID min.	Pipe ID max.		Wall thickness s	V4A pipe rolled da	Max. expanded diameter DA	Rubber thickness	Height of seals
mm Designation	mm Designation.	mm Dg	mm DN min	mm DN max	VP	mm S V4A	mm da	mm DA	mm S Rubber	mm Hn
0100-090 <sup>1</sup>	140 <sup>3</sup>	90	97	107	VP 100-150 VFW	0.8	81	102	1.5	3.0
0100-140 <sup>2</sup>	140	90	97	107	VP 100-150 VFW	0.8	81	102	1.5	3.0
0125-090	140 <sup>3</sup>	109	122	132	VP 100-150 VFW	1	100	127	1.5	3.0
0125-140	140	109	122	132	VP 100-150 VFW	1	100	127	1.5	3.0

<sup>1</sup> Sleeve can be used in bended pipes (bends up to 45°)

<sup>2</sup> Sleeve can only be used in straight pipes

<sup>3</sup> EPDM rubber must be shortened