



QUICK-LOCK Flex DN 200 - DN 600

QL sleeve DN		Rubber Jacket DN	Sleeve length DN	Total diameter rolled Dg	Suitable for pipes from / to		max. radial offset size	Sealed area single installation AE	Packer VP	Stainless steel sleeve			Rubber jacket			Total weight Kg
					Pipe ID min. DN min	Pipe ID max. DN max				Wall thickness S V4A	V4A pipe rolled da	Max. expanded diameter DA	Rubber thickness S Rubber	Height of seals Hn	Rubber thickness incl. seals	
mm	inch	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Kg
DN		Desig.	L	Dg	DN min	DN max	up to	AE	VP	S V4A	da	DA	S Rubber	Hn		
200	8"	200	360	173	196	207	20	320	VP 150-200 VFWL	1,2	159	202	2	5	7	2,47
250	10"	250	360	215	247	261	20	315	VP 200-300 VFWL	1,2	199	252	2	6	8	3,13
300	12"	300	360	256	293	313	25	310	VP 200-300 VFWL	1,2	238	305	2	7	9	3,71
400	16"	400	360	350	390	415	25	310	VP 350-500 VFWL	1,5	330	406	2	8	10	5,75
450	18"	450	360	387	410	465	25	395	VP 350-500 VFWL	2,0	367	455	2	8	10	11,10
500	20"	500	460	448	487	515	25	385	VP 350-500 VFWL / VP 500-600 VFWL	2,0	428	505	2	8	10	12,15
600	24"	600	460	539	582	617	25	390	VP 500-600 VFWL	2,0	519	607	2,5	8	10,5	14,80